



Submittal Data

MODEL
REG-183R01

Project Name:	
Location:	
Engineer:	
Submitted to:	
Submitted by:	

Approval:	
Date:	
Construction:	
Unit #:	
Drawing #:	

Reference:

PERFORMANCE DATA

Power supply 1Ph,230/208V-,60Hz

Cooling

Capacity	Btu/h	18800/18400
Input	W	1760/1720
Rated current	A	9.8/10.8
Max. Current	A	12.10
CEER	Btu/w	10.7

Heating

Capacity	Btu/h	16000/13000
RATED Input(Heater)	W	4800/ 3925
Rated current	A	21.9 / 19.9

Compressor Electrical

Model	KSF160N1VET	
Type	Rotary	
Brand	GMCC	
Capacity	Btu/h	19073
Input	W	1375/1390
Rated current(RLA)	A	6.75/6.1
Refrigerant type	oz	R32/22.58

Air flow & Noise level

Indoor air flow	CFM	449/403/356
Indoor noise level	dB(A)	58.5/57/55
Outdoor air flow	CFM	739/658/581
Outdoor noise level	dB(A)	68.5/67/64.5
Window Opening	Min/Max	26.5/40.5
	Width	
	Min Height	18.5

Accessories

AS080	Window AC Support Bracket
NTN-2	Window AC Support Bracket



Fan Motor

Model	ZKFP-175-8-1L	
Input	W	225
Speed	RPM	1100/1000/90

Dimensional Data

Dimension(W*D*H)	inch	23.62x25.39x17.91
Packing (W*D*H)	inch	29.92x25.98x19.49
Net/Gross weight	lbs.	117.28/131.61

SYSTEM DATA

Design pressure	PSIG	300/520
Thermostat type	Touchpad/Remote	
Application area (Cooling EPA)	700-1000	

Cord and Plug

Cord Length	ft.	6.5
Plug Face	Nema	6-30P

