

# MATERIAL SAFETY DATA SHEET Nashua 324A CW

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATIONS AND OF THE COMPANY UNDERTAKING

Product Name Nashua 324A CW

Product Description Pressure Sensitive Adhesive

Manufacturer/Supplier Berry Plastics Corporation, Tapes and Coatings Division

Address 25 Forge Parkway

Franklin, MA 02038

**Phone Number** (800) 248-7659 (Monday – Friday 8:00 am to 5:00 pm)

 Chemtrec Number
 (800) 424-9300

 Revision Date:
 March 23, 2012

 MSDS Date:
 July 10, 2007

Safety Data Sheet according to EC directive 2001/59/EC and OSHA's Hazcom Standard (29 CFR 1910.1200)

#### 2. HAZARDS IDENTIFICATION

### **EU Main Hazards**

Not classified as hazardous.

### Routes of Entry

Inhalation - Skin contact

#### Carcinogenic Status

Not considered carcinogenic by NTP, IARC, and OSHA.

### **Target Organs**

Skin – Respiratory System – Central Nervous System – Reproductive System

### **Health Effects - Eyes**

Contact may cause irritation due to mechanical abrasion. High concentrations of vapor may cause irritation.

# Health Effects - Skin

Prolonged, repeated contact with adhesive may cause irritation and/or allergic sensitization. Repeated or prolonged contact may produce defatting of the skin leading to irritation and dermatitis. Material can be absorbed through the skin and repeated, prolonged contact may cause adverse reproductive effects.

# **Health Effects - Ingestion**

Not an expected route of entry during normal handling and use.

### **Health Effects - Inhalation**

Exposure to vapor may have the following effects:

- irritation of nose, throat and respiratory tract - central nervous system depression - dizziness - drowsiness - headache - mental confusion

Repeated or prolonged exposure to vapor at high concentrations may have the following effects:

- adverse effects to nervous system - lung damage - adverse reproductive effects

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component NameCAS#/CodesConcentrationR PhrasesClassificationPolymersN.A.<25%</td>NoneNone

Revision Date: March 23, 2012 Page 1 of 6

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Component Name<br>Toluene | <b>CAS#/Codes</b><br>108-88-3<br>203-625-9 | Concentration 0.1 - <1% | <b>R Phrases</b><br>R11, R38, R48/20,<br>R63, R65, R67 | <b>Classification</b> F, Xn, Repro Cat. 3 |
|---------------------------|--|-------------------------|--|---|
| Ethyl Acetate             | 141-78-6<br>205-500-4                      | <2.0%                   | R11,R36,R66,R67  | F, Xi                                     |

### 4. FIRST AID MEASURES

# **Eyes**

Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention if soreness or redness persists.

#### Skin

Wash skin thoroughly with soap and water. Obtain medical attention if blistering occurs or redness persists.

# Ingestion

Obtain medical attention immediately.

### Inhalation

Remove person to fresh air. Seek medical attention if symptoms persist.

### **Advice to Physicians**

Treat symptomatically.

### 5. FIRE - FIGHTING MEASURES

# **Extinguishing Media**

Water spray, carbon dioxide and dry chemical.

# **Unusual Fire and Explosion Hazards**

May release hazardous vapors during a fire.

# **Protective Equipment for Fire-Fighting**

Wear full protective clothing and self-contained breathing apparatus.

### 6. ACCIDENTAL RELEASE MEASURES

No specific measures necessary. Prevent the material from entering drains or watercourses.

# 7. HANDLING AND STORAGE

Keep away from heat and sources of ignition. Storage area should be: - cool - dry - well ventilated - away from incompatible materials

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# **Occupational Exposure Standards**

Exposure limits are listed below, if they exist.

### **Polymer**

None established

### **Ethyl Acetate**

ACGIH: TLV 400 ppm (1440mg/m³) 8h TWA. OSHA: PEL 400ppm (1400mg/m³) 8h TWA

### Toluene

ACGIH: TLV 20 ppm (75mg/m<sup>3</sup>) 8hTWA.

OSHA:PEL 200 ppm 8h TWA, Ceiling (C) 300 ppm, 500ppm 10-min peak per 8-hr shift

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# **Engineering Control Measures**

No specific measures necessary. Good general room ventilation is expected to be adequate to control airborne levels.

# **Respiratory Protection**

Respiratory protection not normally required.

### **Hand Protection**

Not required under normal conditions of use. However, care should be taken to avoid contact with the adhesive.

# **Eye Protection**

Safety glasses

# **Body Protection**

Normal work wear.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State Pressure sensitive adhesive coated onto a foil backing with silicone

coated paper release liner

Color Clear adhesive with silver foil backing and white liner

Odor

pH

Not applicable

Specific Gravity

No data available

Boiling Range/Point (°C/F)

Melting Point (°C/F)

Flash Point (PMCC) (°C/F)

Not applicable

Not known

Explosion Limits (%) No data available Vapor Pressure Not applicable

DensityNo data.VOC (g/l)<30 g/l</th>VOC (%, by weight)<2%</th>Solubility in WaterNot knownVapor Density (Air = 1)Not applicable

### 10. STABILITY AND REACTIVITY

# Stability

Stable under normal conditions.

# **Conditions to Avoid**

Heat - High temperatures

### **Materials to Avoid**

Strong oxidizing agents - acids - bases

# **Hazardous Polymerization**

Will not occur.

# **Hazardous Decomposition Products**

Oxides of carbon – unknown hydrocarbons

### 11. TOXICOLOGICAL INFORMATION

# **Acute Toxicity**

Toluene: Oral LD50 rat >2,000 mg/kg

Dermal LD50 rabbit >3,000 mg/kg Inhalation LC50(rat) 28.1 mg/l 4hr Ethyl Acetate: Oral LD50 (rat) 5,620 mg/kg

# **Specific Target Organ Systemic Toxicity (single and repeat)**

Ethyl acetate: Can cause narcotic effects and respiratory irritation.

# Serious Eye damage/Eye Irritation

No relevant studies identified.

# Skin Corrosion/Irritation

No relevant studies identified.

# Respiratory or Skin Sensitization

No relevant studies identified.

# Carcinogenicity

Toluene: No evidence of carcinogenic activity in laboratory animal studies.

# Germ Cell Mutagenicity

Toluene: Negative Ames Test with and without metabolic activation.

# **Toxicity to Reproduction**

Toluene: In laboratory studies, birth defects, increased fetal lethality and delayed fetal development have been observed in offspring of female animals exposed during pregnancy. Toluene has been demonstrated to be embryofetotoxic and teratogenic in laboratory animals.

### 12. ECOLOGICAL INFORMATION

# Mobility

No relevant studies identified.

### Persistence/Degradability

No relevant studies identified.

### **Bio-accumulation**

No relevant studies identified.

### **Ecotoxicity**

The product may be harmful to aquatic organisms.

# 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with all applicable local and national regulations.

### 14. TRANSPORT INFORMATION

**DOT CFR 172.101 Data UN Proper Shipping Name**Not Regulated

Not Regulated

UN Class None.
UN Number None.
UN Packaging Group None.

Classification for AIR
Transportation (IATA)

Consult current IATA Regulations prior to shipping by air.

Revision Date: March 23, 2012 Page 4 of 6

### 15. REGULATORY INFORMATION

### EU Label Information

Classification and labelling have been performed according to EU directives 67/548/EEC and 99/45/EC including amendments(2001/60/EC and 2006/8/EC)

### **EC Annex I Classification**

According to EC Commission Directive 67/548/EEC this product is not classified.

### R phrases

None.

## S phrases

None.

# US REGULATIONS (Federal, State) and INTERNATIONAL CHEMICAL REGISTRATION LAWS

### **TSCA Listing**

This product contains ingredients that are listed on or exempt from listing on the EPA Toxic Substance Control Act Chemical Inventory.

# **EINECS Listing**

All ingredients in this product have not been verified for listing on the European Inventory of Existing Commercial Chemical Substances (EINECS).

# DSL (Canadian) Listing

All ingredients in this product have not been verified for listing on the Domestic Substance List (DSL).

# **California Proposition 65**

This product contains materials which the State of California has found to cause cancer, birth defects or other reproductive harm.

# SARA Title III Sect. 311/312 Categorization

Immediate (acute) Delayed (Chronic)

# SARA Title III Sect. 313

This product contains the following chemicals that are listed in Section 313 at or above de minimis concentrations: None

### 16. OTHER INFORMATION

# **NFPA Ratings**

NFPA Code for Flammability - 0

NFPA Code for Health - 1

NFPA Code for Reactivity - 0

NFPA Code for Special Hazards - 0

### **HMIS Ratings**

HMIS Code for Flammability - 0

HMIS Code for Health - 1

HMIS Code for Reactivity - 0

HMIS Code for Personal Protection - See Section 8

### **Abbreviations**

N/A: Denotes no applicable information found or available

CAS#: Chemical Abstracts Service Number

ACGIH: American Conference of Governmental Industrial Hygienists

OSHA: Occupational Safety and Health Administration

TLV: Threshold Limit Value
PEL: Permissible Exposure Limit

STEL: Short Term Exposure Limit NTP: National Toxicology Program

IARC: International Agency for Research on Cancer

F: Highly Flammable

Xi: Irritant

# 16. OTHER INFORMATION

# **Abbreviations**

Xn: Harmful R: Risk

R11: Highly Flammable. R36: Irritating to eyes. R38: Irritating to skin.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R63: Possible risk of harm to the unborn child.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

S: Safety

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

BOD: Biological Oxygen Demand

KoC: Soil Organic Carbon Partition Coefficient

For further Information email: msdstechnical@berryplastics.com

Prepared By: EnviroNet LLC.

The information and recommendations presented in this MSDS are based on sources believed to be accurate. Berry Plastics Corporation, Tapes and Coatings Division assumes no liability for the accuracy or completeness of this information. It is the user's responsibility to determine the suitability of the **material** for their particular purposes. In particular, we make NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, with respect to such information, and we assume no liability resulting from its use. Users should ensure that any use **or disposal** of the material is in accordance with applicable Federal, State, and local laws and regulations.

Revision Date: March 23, 2012 Page 6 of 6